По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес: amn@nt-rt.ru | http://apem.nt-rt.ru

"I" RANGE PUSHBUTTON SWITCHES

APEM INNOVATION

IR SERIES
INCREASED VISIBILITY

APEM EXCLUSIVE

- ILLUMINATED BEZEL
- SPECIFIC BACKLIGHTING for visibility in any viewing angle
- LARGE DIAMETER : 16 MM
- FRONT PANEL SEALING
- LARGE CHOICE OF OPTIONS: COLOR, SHAPE, MARKING, ILLUMINATION

OUR RANGE

For more information, see APEM website

SERIES	IC	IL	IM	IP momentary	IP latching	IB	IS	IHS Hall effect	IHL Hall effect
Approvals			UL	UL	UL	UL	UL		
Poles	1	1	1	1	1	1	1	1 NPN	1
Maximum ratings	5A 28VDC	2A 24VDC	(2A 250VAC)* 3A 28VDC	(2A 250VAC)* 5A 28VDC	(2A 250VAC)* 4A 12VDC	(2A 250VAC)* 100mA 48VDC	(2A 250VAC)* 100mA 48VDC	50mA 24VDC	1,25mA 4,5VDC
Illuminated		X		X	X				
Bushing dimensions									
Ø12 (.472)	X	X	X	X	X	X	X	X	X
Mounting options									
Panel	X	X	X	X	X	X	X	X	X
Snap-in						X			
Terminal options									
PCB	X	X	X	X	X	X	X		
Solder lugs	X	X		X	X	X	X		
Quick-connect	X		X	X	X	X	X		
Screw									
Flying leads	X	X		X	X			X	X
Sealing	IP67	IP67	IP67	IP67	IP67	IP54	IP67	IP67	IP67

SERIES	IQ momentary	IQ latching	IZ metal	IZ plastic	IR microswitch	IR standard	IR latching	IA	IF
Approvals									
Poles	1	1	1	1	1	1	1	1	1
Maximum ratings	5A 28VDC	4A 12VDC	4A 48VDC	4A 48VDC	5A 250VAC	5A 28VDC	4A 12VDC	2A 24VDC	100mA 48VDC
Illuminated	X	X	X	X	X	X	X		
Bushing dimensions									
Ø16 (.629)	X	X	X	X	X	X	X	X	X
Mounting options									
Panel			Rear	Rear	X	X	X	X	X
Snap-in	X	X							X
Terminal options									
PCB	X	X	X	X		X	X		
Solder lugs	X	X	X	X		X	X		
Quick-connect	X	X	X	X	X	X	X		X
Screw	X		X	X		X			
Flying leads	X	X	X	X		X	X	X	
Sealing	IP54	IP54	IP67	IP67	IP67	IP67	IP67	IP67	IP67