

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16


Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес: amn@nt-rt.ru | http://apem.nt-rt.ru



TG SERIES TOTALLY SEALED



★ **WASHABLE.**
A totally sealed boot protects the switch during the PCB cleaning process

APEM
EXCLUSIVE

- DESIGNED FOR SURFACE MOUNT
- RESISTANT TO VIBRATIONS

SUBMINIATURE AND SLIDE SWITCHES

OUR RANGE

For more information, see APEM website



SERIES	SMT TL	TL	SMT TP	TP	SMT TR	TR
Approvals						
Poles	1	1,2	1	1,2	1	1,2
Maximum ratings	0,4VA 20V AC/DC	0,5A 48V AC/DC	0,4VA 20V AC/DC	0,5A 48V AC/DC	0,4VA 20V AC/DC	0,5A 48V AC/DC
Mounting options						
Horizontal SMT	X		X		X	
Vertical right angle SMT	X		X			
Vertical Through-hole		X		X		X
Horizontal Through-hole		X		X		X
Vert. right angle TH		X		X		X
Panel						
Terminal options						
PCB	X	X	X	X	X	X
Solder lugs						
Wire wrap		X				
Sealing	Process	Process	Process	Process	Process	Process



SERIES	NK	SMT TG	TG	G	25000N	PHAP 40	PHAP 33
Approvals					UL		
Poles	1	1	1	1,2	1,2	2	1
Maximum ratings	500mA 12VDC	0,4VA 20V AC/DC	0,5A 48V AC/DC	3A 30VDC	(2A 250VAC)* 1A 30VDC	100mA 30VDC	50mA 12VDC
Mounting options							
Horizontal SMT		X					X
Vertical right angle SMT	X		X	X	X		X
Vertical Through-hole	X		X	X	X	X	X
Horizontal Through-hole				X			X
Vert. right angle TH				X			X
Panel				X			
Terminal options							
PCB	X	X	X	X	X	X	X
Solder lugs				X			
Wire wrap				X			
Sealing	No	Process	Process	No	No	No	Process